




















PREFERRED 38999 CIRCULAR CONNECTORS FOR RF HARNESSSES

CABLE TYPE	CONTACT SIZE	38999 SHELL SIZE						
		#25	#23	#21	#19	#17	#15	#11
Storm Flex® 047 & Semi-Rigid 047	#20 MAX FREQUENCY: 60 GHz	 INSERT 25-61 61 Contacts	 INSERT 23-55 55 Contacts	 INSERT 21-41 41 Contacts	×	 INSERT 17-26 26 Contacts	 INSERT 15-19 19 Contacts	 INSERT 11-99 7 Contacts
Storm Flex® 047 & 086, Semi-Rigid 047 & 086	#16 MAX FREQUENCY: 30 GHz	 INSERT 25-37 37 Contacts	 INSERT 23-21 21 Contacts	 INSERT 21-16 16 Contacts	 INSERT 19-11 11 Contacts	 INSERT 17-8 8 Contacts	 INSERT 15-5 5 Contacts	×
Phase Master® 110, True Blue® 125, Storm Flex® 141 & 086, Semi-Rigid 141 & 086	#12 MAX FREQUENCY: 26 GHz	 INSERT 25-19 19 Contacts	×	 INSERT 21-11 11 Contacts	×	 INSERT 17-6 6 Contacts	×	×
Phase Master® 110 & 190, dB Miser™ 210, True Blue® 125 & 205, Storm Flex® 141 & 086, Semi-Rigid 141 & 086	#8 MAX FREQUENCY: 23 GHz	 INSERT 25-8 8 Contacts	 INSERT 23-6 6 Contacts	 INSERT 21-75 4 Contacts	×	×	×	×
38999 Plug Outside Diameter		Ø 1.625"	Ø 1.500"	Ø 1.375"	Ø 1.250"	Ø 1.187"	Ø 1.000"	Ø 0.984"
 = NO SHELL AVAILABLE IN THIS CONFIGURATION								