

## **QP1691A/QP2691/QP3691 (RS-422/RS-423) Line Drivers with Tri-State Outputs**

### **Features**

- Dual RS-422 line driver with mode pin low or Quad RS-423 line driver with mode pin high
- Tri-State Outputs in RS-422 mode
- Outputs will not clamp line with power off or in Tri-State mode
- 100Ω transmission line drive capability
- Low  $I_{CC}$  and  $I_{EE}$  power consumption
  - RS-422:  $I_{CC} = 9$  mA/driver typical
  - RS-423:  $I_{CC} = 4.5$  mA/driver typical  
 $I_{EE} = 2.5$  mA/driver typical
- Short Circuit protection for both source and sink outputs
- Pin Compatible with AM26LS30
- EPROM technology 100% programmable
- Low current PNP inputs compatible with TTL, MOS and CMOS logic

### **General Description**

The QP1691A/QP2691/QP3691 are low power Schottky TTL line drivers designed to meet the requirements of EIA standards RS-422 and RS-423. They feature four buffered outputs with high source and sink current capability with internal short circuit protection. A mode control input provides a choice of operation either as 4 single-ended line drivers or 2 differential line drivers. A rise time control pin allows the use of an external capacitor to slow the rise time for suppression of near end crosstalk to other receivers in the cable. Rise time capacitors are primarily intended for wave shaping output signals in the single-ended driver mode. A multipoint application in differential mode with wave shaping capacitors is not allowed.

With the mode select pin low, the QP1691A/QP2691/QP3691 are dual-differential line drivers with TRI-STATE outputs. They feature  $\pm 10V$  output common-mode range in Tri-State mode and 0V output unbalance when operated with  $\pm 5V$  supply.

---

*QP Semiconductor products are not authorized for use in any space applications. The inclusion of QP Semiconductor products in space applications implies that the space application manufacturer assumes all risk of such use and in doing so indemnifies QP Semiconductor against all charges.*

---

## Connection Diagrams

|   | With Mode Select LOW<br>(RS-422 Connection) | With Mode Select HIGH<br>(RS-423 Connection) |
|---|---|--|
| QP1691A<br>QP2691<br>QP3691<br><br>CerDIP<br>PDIP<br>Cerpack<br>SOIC<br><br>16 Lead | <p style="text-align: center;">Top View</p> | <p style="text-align: center;">Top View</p>  |
| QP1691A<br>QP2691<br>QP3691<br><br>LCC<br><br>20 Lead                               |   |  |

### Absolute Maximum Ratings

Stresses above the AMR may cause permanent damage, extended operation at AMR may degrade performance and affect reliability

| Condition                         | /5   | Units          | Notes |
|-----------------------------------|------|----------------|-------|
| V <sub>CC</sub> Supply Voltage    |      | 7.0 Volts      |       |
| V <sub>EE</sub> Supply Voltage    |      | -7.0 Volts     |       |
| Maximum Power Dissipation at 25°C |      |                |       |
| CerDIP                            | 1509 | mW/°C          | /1    |
| Molded DIP                        | 1476 | mW/°C          |       |
| SOIC                              | 1051 | mW/°C          |       |
| DC Input Voltage                  |      | 15 Volts       |       |
| Output Voltage Power Off          |      | ±15 Volts      |       |
| Storage Temperature               |      | -65 to +155 °C |       |
| Junction Temperature              |      |                |       |
| Hermetic Packages                 | 175  | °C             | /2    |
| Molded Packages                   | 160  | °C             | /2 /3 |

**Recommended Operating Conditions**

| Condition                                | /1 /2 /5   | Units                | Notes                           |
|--|--|----------------------|---------------------------------|
| Supply Voltage Range<br>QP1691A          | $V_{CC}$ 4.5 to 5.5<br>$V_{EE}$ -4.5 to -5.5     | Volts DC<br>Volts DC | $5V \pm 10\%$<br>$-5V \pm 10\%$ |
| QP2691/QP3691                            | $V_{CC}$ 4.75 to 5.25<br>$V_{EE}$ -4.75 to -5.25 | Volts DC<br>Volts DC | $5V \pm 5\%$<br>$-5V \pm 5\%$   |
| Case Operating Range ( $T_c$ ) (QP3691)  | -0C to +70                                       | °C                   | Commercial                      |
| Case Operating Range ( $T_c$ ) (QP2691)  | -40C to +85                                      | °C                   | Industrial                      |
| Case Operating Range ( $T_c$ ) (QP1691A) | -55 to +125                                      | °C                   | Military                        |

**Notes:**

Apply to Absolute Maximum, Recommended Operating Conditions and Electrical Performance Characteristics.

- /1 – Derate CerDIP package 10.1mW/°C above 25°C; derate molded DIP package 11.9mW/°C above 25°C; derate SO package 8.41mW/°C above 25°C.
- /2 – Maximum  $T_j$  is not to be exceeded.
- /3 – Critical for molded plastic products.  $T_j$  above listed limits can activate mold compound flame retardant.
- /4 – Supply Voltage Range per above table.
- /5 – “Absolute Maximum Ratings” are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the devices should be operated at these limits. “Electrical Performance Characteristics” provide conditions for actual device operation.
- /6 – Unless otherwise specified, min/max limits apply across the -55°C to +125°C temperature range for the QP1691A, across the -40°C to +85°C temperature range for the QP2691 and across the 0°C to +70°C temperature range for the QP3691
- /7 – All currents into device pins are positive; all currents out of device pins are negative. All voltages referenced to ground unless otherwise specified.
- /8 – Only one output at a time should be shorted.
- /9 – Symbols and definitions correspond to EIA RS-422 and/or RS-423 where applicable.
- /10 – At -55°C, the output voltage is +3.9V minimum and -3.9V maximum.

**TABLE I – ELECTRICAL PERFORMANCE CHARACTERISTICS**

| Test                                 | Symbol    | Conditions /4 /6 /7 /8 /9<br>Case Operating Range (°C) | Min | Max  | Unit |
|--------------------------------------|-----------|--|-----|------|------|
| RS-422 Connection                    |           | $V_{EE}$ to GND,<br>Mode Select $\leq 0.8V$            |     |      |      |
| <b>DC Electrical Characteristics</b> |           |  |     |      |      |
| Input High Voltage                   | $V_{IH}$  | Guaranteed Input logical High for all inputs           | 2.0 |      | V    |
| Input Low Voltage                    | $V_{IL}$  | Guaranteed Input logical Low for all inputs            |     | 0.8  | V    |
| High Level Input Current             | $I_{IH}$  | $V_{IN} = 2.4V$  |     | 40   | uA   |
|                                      | $I_{IH1}$ | $V_{IN} \leq 15.0V$                                    |     | 100  | uA   |
| Low Level Input Current              | $I_{IL}$  | $V_{IN} = 0.4V$  |     | -200 | uA   |
| Input Clamp Voltage                  | $V_I$     | $I_{IN} = -12mA$                                       |     | -1.5 | V    |

**TABLE I – ELECTRICAL PERFORMANCE CHARACTERISTICS**

| Test                                      | Symbol                                   | Conditions /4 /6 /7 /8 /9<br>Case Operating Range (°C) | Min      | Max  | Unit    |
|---|--|--|----------|------|---------|
| Differential Output Voltage $V_{A,B}$     | $V_O$                                    | $R_L = \infty$ $V_{IN} = 2.0V$                         |          | 6.0  | V       |
|   | $V_{O\overline{BAR}}$                    | $V_{IN} = 0.8V$  |          | -6.0 | V       |
| Differential Output Voltage $V_{A,B}$     | $V_T$                                    | $R_L = 100\Omega$ $V_{IN} = 2.0V$                      | 2        |      | V       |
|   | $V_{T\overline{BAR}}$                    | $V_{CC} \geq 4.75V$ $V_{IN} = 0.8V$                    | -2       |      | V       |
| Common-Mode Offset Voltage                | $V_{OS},$<br>$V_{OS\overline{BAR}}$      | $R_L = 100\Omega$                                      |          | 3    | V       |
| Difference in Differential Output Voltage | $ V_T  -$<br>$ V_{T\overline{BAR}} $     | $R_L = 100\Omega$                                      |          | 0.4  | V       |
| Difference in Common-Mode Offset Voltage  | $ V_{OS}  -$<br>$ V_{OS\overline{BAR}} $ | $R_L = 100\Omega$                                      |          | 0.4  | V       |
| $ V_T - V_{T\overline{BAR}} $             | $V_{SS}$                                 | $R_L = 100\Omega, V_{CC} \geq 4.75V$                   | 4.0      |      | V       |
| Output Voltage Common-Mode Range          | $V_{CMR}$                                | $V_{DISABLE} = 2.4V$                                   | $\pm 10$ |      | V       |
| Output Leakage Current<br>Power Off       | $I_{XA}$                                 | $V_{CC} = 0V, V_{CM} = 10V$                            |          | 100  | $\mu A$ |
|   | $I_{XB}$                                 | $V_{CC} = 0V, V_{CM} = -10V$                           |          | -100 | $\mu A$ |
| Tri-State Output Current                  | $I_{OX}$                                 | $V_{CC} = \text{Max}$ $V_{CM} \leq 10V$                |          | 100  | $\mu A$ |
|   |  | $V_{ee} = 0\&-5V$ $V_{CM} \geq -10V$                   |          | -100 | $\mu A$ |
| Output Short Circuit Current              | $I_{SA}$                                 | $V_{IN} = 0.4V, V_{OA} = 6V$                           | 80       | 150  | mA      |
|   |  | $V_{IN} = 0.4V, V_{OB} = 0V$                           | -80      | -150 | mA      |
| Output Short Circuit Current              | $I_{SB}$                                 | $V_{IN} = 2.4V, V_{OA} = 0V$                           | -80      | -150 | mA      |
|   |  | $V_{IN} = 2.4V, V_{OB} = 6V$                           | 80       | 150  | mA      |

**TABLE I – ELECTRICAL PERFORMANCE CHARACTERISTICS**

| Test                                 | Symbol                      | Conditions /4 /6 /7 /8 /9<br>Case Operating Range (°C)                     | Min  | Max  | Unit          |
|--------------------------------------|-----------------------------|--|------|------|---------------|
| Operating Supply Current             | $I_{CC}$                    | $V_{CC} = 5.5V, I_{OUT} = 0 \text{ mA}$                                    |      | 30   | mA            |
| <b>AC Electrical Characteristics</b> |                             | $T_A = 25^\circ\text{C}$ /9  |      |      |               |
| Output Rise Time                     | $t_r$                       | $R_L = 100\Omega, C_L = 500 \text{ pF}$<br>(Figure 1)                      |      | 200  | ns            |
| Output Fall Time                     | $T_f$                       | $R_L = 100\Omega, C_L = 500 \text{ pF}$<br>(Figure 1)                      |      | 200  | ns            |
| Output Propagation Delay             | $T_{PDH}$                   | $R_L = 100\Omega, C_L = 500 \text{ pF}$<br>(Figure 1)                      |      | 200  | ns            |
| Output Propagation Delay             | $T_{PDL}$                   | $R_L = 100\Omega, C_L = 500 \text{ pF}$<br>(Figure 1)                      |      | 200  | ns            |
| Tri-State Delay                      | $T_{PZL}$                   | $R_L = 450\Omega, C_L = 500 \text{ pF}$<br>$C_C = 0 \text{ pF}$ (Figure 4) |      | 350  | ns            |
| Tri-State Delay                      | $T_{PZH}$                   | $R_L = 450\Omega, C_L = 500 \text{ pF}$<br>$C_C = 0 \text{ pF}$ (Figure 4) |      | 350  | ns            |
| Tri-State Delay                      | $T_{PLZ}$                   | $R_L = 450\Omega, C_L = 500 \text{ pF}$<br>$C_C = 0 \text{ pF}$ (Figure 4) |      | 350  | ns            |
| Tri-State Delay                      | $T_{PHZ}$                   | $R_L = 450\Omega, C_L = 500 \text{ pF}$<br>$C_C = 0 \text{ pF}$ (Figure 4) |      | 350  | ns            |
| <b>RS-423 Connection</b>             |                             |  |      |      |               |
|                                      |                             | $ V_{CC}  =  V_{EE} ,$<br>Mode Select $\geq 2V$                            |      |      |               |
| <b>DC Electrical Characteristics</b> |                             |  |      |      |               |
| Input High Voltage                   | $V_{IH}$                    | Guaranteed Input logical<br>High for all inputs                            | 2.0  |      | V             |
| Input Low Voltage                    | $V_{IL}$                    | Guaranteed Input logical<br>Low for all inputs                             |      | 0.8  | V             |
| High Level Input Current             | $I_{IH}$                    | $V_{IN} = 2.4V$  |      | 40   | $\mu\text{A}$ |
|                                      | $I_{IH1}$                   | $V_{IN} \leq 15.0V$  |      | 100  | $\mu\text{A}$ |
| Low Level Input Current              | $I_{IL}$                    | $V_{IN} = 0.4V$  |      | -200 | $\mu\text{A}$ |
| Input Clamp Voltage                  | $V_I$                       | $I_{IN} = -12\text{mA}$  |      | -1.5 | V             |
| Output Voltage                       | $V_O$                       | $R_L = \infty /10 \quad V_{IN} = 2.0V$                                     | 4.0  | 6.0  | V             |
|                                      | $V_{O\text{BAR}}$           | $V_{IN} = 0.4V$  | -4.0 | -6.0 | V             |
| Output Voltage                       | $V_T$                       | $R_L = 450\Omega \quad V_{IN} = 2.0V$                                      | 3.6  |      | V             |
|                                      | $V_{T\text{BAR}}$           | $V_{CC} \geq 4.75V \quad V_{IN} = 0.8V$                                    | -3.6 |      | V             |
| Output Unbalance                     | $ V_T  -  V_{T\text{BAR}} $ | $ V_{CC}  =  V_{EE}  = 4.75V,$<br>$R_L = 450\Omega$                        |      | 0.4  | V             |

**TABLE I – ELECTRICAL PERFORMANCE CHARACTERISTICS**

| Test                                 | Symbol           | Conditions / 4 / 6 / 7 / 8 / 9<br>Case Operating Range (°C)        | Min  | Max  | Unit       |
|--------------------------------------|------------------|--|------|------|------------|
| Output Leakage Power OFF             | $I_{X+}$         | $V_{CC}=V_{EE}= 0V, V_O= 6V$                                       |      | 100  | $\mu A$    |
|                                      | $I_{X+}$         | $V_{CC}=V_{EE}= 0V, V_O= -6V$                                      |      | -100 | $\mu A$    |
| Output Short Circuit Current         | $I_{S+}$         | $V_{IN}= 2.4V, V_O= 0V$  |      | -150 | mA         |
|                                      | $I_{S-}$         | $V_{IN}= 0.4V, V_O= 0V$  |      | 150  | mA         |
| Slew Control Current                 | $I_{SLEW}$       | Typical  | -140 | 140  | $\mu A$    |
| Positive Supply Current              | $I_{CC}$         | $V_{IN}= 0.4V, R_L= \infty$  |      | 30   | mA         |
| Negative Supply Current              | $I_{EE}$         | $V_{IN}= 0.4V, R_L= \infty$  |      | -22  | mA         |
| <b>AC Electrical Characteristics</b> | $T_A=25^\circ C$ | /9   |      |      |            |
| Output Rise Time                     | $t_r$            | $R_L= 450\Omega, C_L= 500\text{ pF}, C_C= 0\text{ pF}$ (Figure 2)  |      | 300  | ns         |
| Output Fall Time                     | $T_f$            | $R_L= 450\Omega, C_L= 500\text{ pF}, C_C= 0\text{ pF}$ (Figure 2)  |      | 300  | ns         |
| Output Rise Time (Typical)           | $t_{r1}$         | $R_L= 450\Omega, C_L= 500\text{ pF}, C_C= 50\text{ pF}$ (Figure 3) |      | 3    | $\mu s$    |
| Output Fall Time (Typical)           | $T_{f1}$         | $R_L= 450\Omega, C_L= 500\text{ pF}, C_C= 50\text{ pF}$ (Figure 3) |      | 3    | $\mu s$    |
| Rise Time Coefficient (Typical)      | $T_{rc}$         | $R_L= 450\Omega, C_L= 500\text{ pF}, C_C= 50\text{ pF}$ (Figure 3) |      | 0.06 | $\mu s/pF$ |
| Output Propagation Delay             | $T_{PDH}$        | $R_L= 450\Omega, C_L= 500\text{ pF}, C_C= 0\text{ pF}$ (Figure 2)  |      | 300  | ns         |
| Output Propagation Delay             | $T_{PDL}$        | $R_L= 450\Omega, C_L= 500\text{ pF}, C_C= 0\text{ pF}$ (Figure 2)  |      | 300  | ns         |

**AC Test Loads**





FIGURE 1. Differential Connection





FIGURE 2. RS-423 Connection





FIGURE 3. Rise Time Control for RS-423





FIGURE 4. TRI-STATE Delays




FIGURE 5. Typical Output Voltage


### Truth Table

| Operation | Inputs |       |       | Outputs   |           |
|-----------|--------|-------|-------|-----------|-----------|
|           | Mode   | A (D) | B (C) | A (D)     | B (C)     |
| RS-422    | 0      | 0     | 0     | 0         | 1         |
|           | 0      | 0     | 1     | TRI-STATE | TRI-STATE |
|           | 0      | 1     | 0     | 1         | 0         |
|           | 0      | 1     | 1     | TRI-STATE | TRI-STATE |
| RS-423    | 1      | 0     | 0     | 0         | 0         |
|           | 1      | 0     | 1     | 0         | 1         |
|           | 1      | 1     | 0     | 1         | 0         |
|           | 1      | 1     | 1     | 1         | 1         |



# Typical Rise Time Control Characteristics (RS-423 Mode)

## Rise Time vs External Capacitor



**Ordering Information**

| Temp Range | Part Number    | Package                     | Mil-Std-1835 | Generic |
|------------|----------------|-----------------------------|--------------|---------|
| Military   | 5962-86721012A | 20-Lead LCC                 | CQCC1-N20    | 1691A   |
| Military   | 5962-8672101EA | 16-Lead 300-mil CerDIP      | GDIP3-T16    | 1691A   |
| Military   | 5962-8672101FA | 16-Lead Flatpack            | GDFP2-F16    | 1691A   |
| Military   | QP1691AE/883   | 20-Lead LCC                 | CQCC1-N20    | 1691A   |
| Military   | QP1691AJ/883   | 16-Lead 300-mil CerDIP      | GDIP3-T16    | 1691A   |
| Military   | QP1691AW/883   | 16-Lead Flatpack            | GDFP2-F16    | 1691A   |
| Industrial | QP2691E        | 20-Lead LCC                 | CQCC1-N20    | 2691    |
| Industrial | QP2691J        | 16-Lead 300-mil CerDIP      | GDIP3-T16    | 2691    |
| Industrial | QP2691W        | 16-Lead Flatpack            | GDFP2-F16    | 2691    |
| Commercial | QP3691J        | 16-Lead 300-mil CerDIP      | GDIP3-T16    | 3691    |
| Commercial | QP3691N        | 16-Lead 300-mil Plastic DIP |              | 3691    |
| Commercial | QP3691M        | 16-Lead SOIC                |              | 3691    |

\* denotes Lead Free Lead Finish

In addition to those products listed above, QP Semiconductor supports Industrial Temperature Range, Source Control Drawing SCD, and custom package development for this product family.

**Notes:**

Hermetic Package outline information and specifications are defined by Mil-Std-1835 package dimension requirements.

Military Products manufactured by QP Semiconductor are compliant to the assembly, burn-in, test and quality conformance requirements of Test Methods 5004 & 5005 of Mil-Std-883 for Class B or Q devices as appropriate. The appropriate DSCC Detail Specifications define the electrical test requirements for each device.

The listed drawings, Mil-PRF-38535, Mil-Std-883 and Mil-Std-1835 are available online at <http://www.dsccl.dla.mil/>

Additional information is available at our website <http://www.qpsemi.com>